

Tools and Materials Recommended for Installation:

A Team of Two Persons Will Ease the Assembly & Installation Process

- Variable Speed Drill & Drill Bits
- Screwdrivers (Phillips & Flat Head)
- Level, Tape Measure, Stud Finder
- Clear Silicone Caulk/Sealant*
- Faucet and Drain Connections
- Adjustable Wrench
- Hardware to Secure to Wall (Suggest 3/16" x 2 1/2" Lag Bolt)

* Do not use plumber's putty

Step 1: Attach Feet/Legs to Vanity

- Remove the box from the inside of the vanity.
- Carefully lie the vanity on it's back on a protected surface.
- **Bun Feet** - Simply manually screw in the bun feet into the bottom of cabinet.

Step 2: Locate Wall Studs

- Determine the exact area on the wall where the cabinet is to be placed.
- Locate at least one (1) wall stud within the desired area.
- If a wall stud is not present, we recommend toggle bolts or an appropriate wall anchor.

Step 3: Install Vanity

- Use the adjustable glides to level the vanity.
- Drill 1/4" diameter hole in vanity back wall/back rail. Drill 1/8" diameter pilot hole into center of stud.
- Note: As you drill holes into wall, use caution to avoid damaging water line/drainage system or electrical wires.
- Fasten the vanity to the wall studs through inside of cabinet.

Step 4: Install the Faucet & Drain

- Install the faucet, drain and supply lines per manufacturer's instructions (if the faucet requires plumber's putty use clear silicone caulk/sealant* instead).
- Place ring of caulk/sealant around drain flange.
- Tighten securely. Avoid over-tightening as it can result in damage to the finish.
- Wipe off excess sealant.

*Plumber's putty contains oils that can cause damage to the finish.

Care, Sealing & Maintenance for Vanity Top

- The vanity top is made from real stone slabs. Due to its natural beauty, every stone top will have its own unique characteristics such as veining, color variances and natural surface textures.
- It is strongly recommended that a stone penetrating sealer be applied to the vanity top. All natural stone products require resealing as a routine maintenance procedure. Top must be clean, dry and free of debris before application. Maintain sealer applications approximately once a year. Follow sealer manufacturer's recommendations.

Cleaning Instructions:

Vanity Top & Porcelain Bowl: Use a mild non-abrasive cleaner with a soft cloth.

Vanity: Use a water-dampened cloth. Avoid using any abrasive cleaners.